


[English](#) | [简体中文](#) | [日本語](#) | [繁體中文](#) | [한국어](#)
[Login](#) | [Register](#)

[Products](#)
[Applications](#)
[Topologies](#)
[Design Support](#)
[Green Room](#)
[Community](#)
[Sales](#)
[Company](#)

[Home](#) » [Products](#) » [TOPSwitch Family](#)
[InnoSwitch Family](#)
[InnoMux Family](#)
[LinkSwitch Family](#)
[TOPSwitch Family](#)
[TOPSwitch-JX](#)
[TOPSwitch-HX](#)
[Hiper Family](#)
[TinySwitch Family](#)
[ChiPhy Family](#)
[CAPZero Family](#)
[SENZero Family](#)
[Qspeed Diodes](#)
[LinkZero Family](#)
[DPA-Switch](#)
[Product Archive](#)



PARAMETRIC SEARCH

## TOPSwitch Family

The latest generation of our flagship TOPSwitch™ series of high efficiency integrated power conversion ICs is TOPSwitch-JX. TOPSwitch-JX incorporates a 725 V power MOSFET and full-featured, multi-mode controller to achieve excellent no-load performance and high efficiency across the entire load range.

TOPSwitch products are suitable for applications such as LCD monitors, LCD TV main or standby, adapters, set-top boxes, audio amplifiers, video games, printers and a wide variety of flyback power supplies from 0 to around 200 W.

### Compare TOPSwitch Products

	TOPSwitch-JX	TOPSwitch - HX
Data Sheet		
BV <sub>DSS</sub>	725 V	700 V
Surface Mount	✓	
Packages	eSIP-7 eDIP-12 eSOP-12	eSIP-7 SMD-8 SDIP-10

By using our website you accept our use of cookies.

[Cookie Policy](#)

Recommended  
for new designs



TOPSwitch-HX



TOPSwitch-JX



PARAMETRIC SEARCH



- Home
- Products
- Applications
- Topologies
- Design Support
- Green Room
- Community
- Sales
- Company

- Sales
- Distributors
- Contact Us

- Careers
- Privacy Policy
- Cookie Policy
- Terms of Use
- UK Modern Slavery Act Statement

By using our website you accept our use of cookies.

[Cookie Policy](#)

Accept