

TYPES SN54ALS640A THRU SN54ALS645A, SN54AS640 THRU SN54AS645 SN74ALS640A THRU SN74ALS645A, SN74AS640 THRU SN74AS645 OCTAL BUS TRANSCEIVERS

D2661, DECEMBER 1983

- Bidirectional Bus Transceivers in High-Density 20-Pin Packages
- Choice of True or Inverting Logic
- Choice of 3-State or Open-Collector Outputs
- Package Options Include Both Plastic and Ceramic Chip Carriers in Addition to Plastic and Ceramic DIPs
- Dependable Texas Instruments Quality and Reliability

DEVICE	OUTPUT	LOGIC
'ALS640A, 'AS640	3-State	Inverting
'ALS641A, 'AS641	Open-Collector	True
'ALS642A, 'AS642	Open-Collector	Inverting
'ALS643A, 'AS643	3-State	True and Inverting
'ALS644A, 'AS644	Open-Collector	True and Inverting
'ALS645A, 'AS645	3-State	True

description


These octal bus transceivers are designed for asynchronous two-way communication between data buses. The devices transmit data from the A bus to the B bus or from the B bus to the A bus depending upon the level at the direction control (DIR) input. The enable input (\bar{G}) can be used to disable the device so the buses are effectively isolated.

The -1 versions of the SN74ALS' parts are identical to the standard versions except that the recommended maximum I_{OL} is increased to 48 milliamperes. There are no -1 versions of the SN54ALS' parts.

The SN54' family is characterized for operation over the full military temperature range of -55°C to 125°C. The SN74' family is characterized for operation from 0°C to 70°C.


SN54ALS', SN54AS' . . . J PACKAGE
SN74ALS', SN74AS' . . . N PACKAGE

(TOP VIEW)



SN54ALS', SN54AS' . . . FH PACKAGE
SN74ALS', SN74AS' . . . FN PACKAGE

(TOP VIEW)




FUNCTION TABLE

CONTROL INPUTS	OPERATION		
	'ALS640A, 'AS640	'ALS641A, 'AS641	'ALS643A, 'AS643
\bar{G} DIR	'ALS642A, 'AS642	'ALS645A, 'AS645	'ALS644A, 'AS644
L L	\bar{B} data to A bus	B data to A bus	B data to A bus
L H	\bar{A} data to B bus	A data to B bus	\bar{A} data to B bus
H X	Isolation	Isolation	Isolation


**TYPES SN54ALS640A THRU SN54ALS645A, SN54AS640 THRU SN54AS645
SN74ALS640A THRU SN74ALS645A, SN74AS640 THRU SN74AS645
OCTAL BUS TRANSCEIVERS**

logic symbols


'ALS640A, 'AS640




'ALS641A, 'AS641




'ALS642A, 'AS642




'ALS643A, 'AS643



'ALS644A, 'AS644



'ALS645A, 'AS645




2


ALS AND AS CIRCUITS

functional block diagrams (positive logic)


'ALS640A, 'AS640




'ALS641A, 'AS641




'ALS642A, 'AS642




'ALS643A, 'AS643



'ALS644A, 'AS644



'ALS645A, 'AS645



Pin numbers shown are for J and N packages.

**TYPES SN54ALS640A THRU SN54ALS645A
SN74ALS640A THRU SN74ALS645A
OCTAL BUS TRANSCEIVERS**

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: All inputs	7 V
I/O ports	5.5 V
Operating free-air temperature range: SN54ALS640A, SN54ALS643A, SN54ALS645A	-55 °C to 125 °C
SN74ALS640A, SN74ALS643A, SN74ALS645A	0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

recommended operating conditions

		SN54ALS640A SN54ALS643A SN54ALS645A			SN74ALS640A SN74ALS643A SN74ALS645A			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage	0.8			0.8			V
I_{OH}	High-level output current	-12			-15			mA
I_{OL}	Low-level output current	12			24			mA
					48†			
T_A	Operating free-air temperature	-55			125			°C

†The extended limits apply only if V_{CC} is maintained between 4.75 V and 5.25 V.
The 48-mA limit applies for the SN74ALS640A-1, SN74ALS643A-1, and SN74ALS645A-1 only.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS*		SN74ALS*		UNIT		
		MIN	TYP‡	MAX	MIN		TYP‡	MAX
V_{IK}	$V_{CC} = 4.5$ V, $I_I = -18$ mA	-1.5		-1.5		V		
V_{OH}	$V_{CC} = 4.5$ V to 5.5 V, $I_{OH} = -0.4$ mA	$V_{CC}-2$		$V_{CC}-2$		V		
	$V_{CC} = 4.5$ V, $I_{OH} = -3$ mA	2.4	3.2	2.4	3.2			
	$V_{CC} = 4.5$ V, $I_{OH} = -12$ mA	2						
	$V_{CC} = 4.5$ V, $I_{OH} = -15$ mA			2				
V_{OL}	$V_{CC} = 4.5$ V, $I_{OL} = 12$ mA	0.25	0.4	0.25	0.4	V		
	$V_{CC} = 4.5$ V, $I_{OL} = 24$ mA			0.35	0.5			
	($I_{OL} = 48$ mA for -1 versions)							
I_I	Control inputs	$V_{CC} = 5.5$ V, $V_I = 7$ V		0.1		mA		
	A or B ports	$V_{CC} = 5.5$ V, $V_I = 5.5$ V		0.1				
I_{IH}	Control inputs	$V_{CC} = 5.5$ V, $V_I = 2.7$ V		20		µA		
	A or B ports‡			20				
I_{IL}	Control inputs	$V_{CC} = 5.5$ V, $V_I = 0.4$ V		-0.1		mA		
	A or B ports‡			-0.1				
I_{O1}	$V_{CC} = 5.5$ V, $V_O = 2.25$ V	-30	-112	-30	-112	mA		
I_{CC}	'ALS640A	$V_{CC} = 5.5$ V	Outputs high	19	35	19	30	mA
			Outputs low	27	45	27	40	
			Outputs disabled	28	48	28	43	
	'ALS643A		Outputs high	25	37	25	35	
			Outputs low	33	47	33	45	
			Outputs disabled	35	50	35	48	
	'ALS645A		Outputs high	30	48	30	45	
			Outputs low	36	60	36	55	
			Outputs disabled	38	63	38	58	

‡All typical values are at $V_{CC} = 5$ V, $T_A = 25$ °C

§For I/O ports, the parameters I_{IH} and I_{IL} include the off-state output current.

†The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

2
ALS AND AS CIRCUITS

**TYPES SN54ALS640A THRU SN54ALS645A
SN74ALS640A THRU SN74ALS645A
OCTAL BUS TRANSCEIVERS**

***ALS640A switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_1 = 500 \Omega,$ $R_2 = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54ALS640A		SN74ALS640A		
			MIN	MAX	MIN	MAX	
t_{PLH}	A or B	B or A	2	14	2	11	ns
t_{PHL}			2	13	2	10	
t_{PZH}	\bar{G}	A or B	5	25	5	21	ns
t_{PZL}			8	27	8	24	
t_{PHZ}	\bar{G}	A or B	2	12	2	10	ns
t_{PLZ}			3	20	3	15	

***ALS643A switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_1 = 500 \Omega,$ $R_2 = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54ALS643A		SN74ALS643A		
			MIN	MAX	MIN	MAX	
t_{PLH}	A	B	2	15	2	13	ns
t_{PHL}			2	13	2	11	
t_{PLH}	B	A	2	15	2	13	ns
t_{PHL}			2	13	2	11	
t_{PZH}	\bar{G}	A	5	28	5	25	ns
t_{PZL}			5	28	5	25	
t_{PHZ}	\bar{G}	A	2	12	2	10	ns
t_{PLZ}			3	22	3	17	
t_{PZH}	\bar{G}	B	5	28	5	25	ns
t_{PZL}			5	28	5	25	
t_{PHZ}	\bar{G}	B	2	12	2	10	ns
t_{PLZ}			3	22	3	17	

***ALS645A switching characteristics (see Note 1)**

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_1 = 500 \Omega,$ $R_2 = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54ALS645A		SN74ALS645A		
			MIN	MAX	MIN	MAX	
t_{PLH}	A or B	B or A	3	15	3	10	ns
t_{PHL}			3	13	3	10	
t_{PZH}	\bar{G}	A or B	5	25	5	20	ns
t_{PZL}			5	25	5	20	
t_{PHZ}	\bar{G}	A or B	2	12	2	10	ns
t_{PLZ}			4	18	4	15	

NOTE 1: For load circuit and voltage waveforms, see page 1-12.

2

ALS AND AS CIRCUITS

**TYPES SN54ALS640A THRU SN54ALS645A
SN74ALS640A THRU SN74ALS645A
OCTAL BUS TRANSCEIVERS**

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: All inputs and I/O ports	7 V
Operating free-air temperature range: SN54ALS641A, SN54ALS642A, SN54ALS644A	-55 °C to 125 °C
SN74ALS641A, SN74ALS642A, SN74ALS644A	0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

recommended operating conditions

		SN54ALS641A SN54ALS642A SN54ALS644A			SN74ALS641A SN74ALS642A SN74ALS644A			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.8			0.8	V
V_{OH}	High-level output voltage			5.5			5.5	V
I_{OL}	Low-level output current			12			24 48†	mA
T_A	Operating free-air temperature	-55		125	0		70	°C

† The extended limits apply only if V_{CC} is maintained between 4.75 and 5.25 V.
The 48-mA limit applies for the SN74ALS641A-1, SN74ALS642A-1, and SN74ALS644A-1 only.

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54ALS641A SN54ALS642A SN54ALS644A		SN74ALS641A SN74ALS642A SN74ALS644A		UNIT		
		MIN	TYP‡	MAX	MIN		TYP‡	MAX
V_{IK}	$V_{CC} = 4.5$ V, $I_I = -18$ mA			-1.5		-1.5	V	
I_{OH}	$V_{CC} = 4.5$ V, $V_{OH} = 5.5$ V			0.1		0.1	mA	
V_{OL}	$V_{CC} = 4.5$ V, $I_{OL} = 12$ mA		0.25	0.4		0.25	0.4	V
	$V_{CC} = 4.5$ V, $I_{OL} = 24$ mA ($I_{OL} = 48$ mA for -1 versions)					0.35	0.5	
I_I	Control inputs A or B ports	$V_{CC} = 5.5$ V,	$V_I = 7$ V			0.1	0.1	mA
		$V_{CC} = 5.5$ V,	$V_I = 5.5$ V			0.1	0.1	
I_{IH}	Control inputs A or B ports‡	$V_{CC} = 5.5$ V,	$V_I = 2.7$ V			20	20	µA
						20	20	
I_{IL}	Control inputs A or B ports‡	$V_{CC} = 5.5$ V,	$V_I = 0.4$ V			-0.1	-0.1	mA
						-0.1	-0.1	
I_{CC}	'ALS641A	$V_{CC} = 5.5$ V	Outputs high	25	40	25	37	mA
			Outputs low	33	50	33	47	
	'ALS642A		Outputs high	8	15	8	15	
			Outputs low	18	28	18	28	
	'ALS644A		Outputs high	16	32	16	29	
			Outputs low	25	44	25	40	

‡ All typical values are at $V_{CC} = 5$ V, $T_A = 25$ °C.
§ For I/O ports, the parameters I_{IH} and I_{IL} include the off-state output current.

2

ALS AND AS CIRCUITS

**TYPES SN54ALS640A THRU SN54ALS645A
SN74ALS640A THRU SN74ALS645A
OCTAL BUS TRANSCEIVERS**

'ALS641A switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 680 Ω, T _A = MIN to MAX				UNIT
			SN54ALS641A		SN74ALS641A		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	5	30	5	25	ns
t _{PHL}			3	23	3	18	
t _{PLH}	\bar{C}	A or B	8	35	8	30	ns
t _{PHL}			8	35	8	30	
t _{PLH}	DIR	A or B	8	37	8	32	ns
t _{PHL}			8	37	8	32	

'ALS642A switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 680 Ω, T _A = MIN to MAX				UNIT
			SN54ALS642A		SN74ALS642A		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	10	35	10	30	ns
t _{PHL}			5	25	5	22	
t _{PLH}	\bar{C} or DIR	A or B	10	35	10	30	ns
t _{PHL}			15	43	15	38	

'ALS644A switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	V _{CC} = 4.5 V to 5.5 V, C _L = 50 pF, R _L = 680 Ω, T _A = MIN to MAX				UNIT
			SN54ALS644A		SN74ALS644A		
			MIN	MAX	MIN	MAX	
t _{PLH}	A	B	10	35	10	30	ns
t _{PHL}			5	25	5	22	
t _{PLH}	B	A	10	35	10	30	ns
t _{PHL}			5	23	5	21	
t _{PLH}	\bar{C}	A	8	35	8	30	ns
t _{PHL}			10	38	10	35	
t _{PLH}	\bar{C}	B	8	31	8	26	ns
t _{PHL}			15	40	15	35	
t _{PLH}	DIR	A	8	31	8	26	ns
t _{PHL}			10	40	10	35	
t _{PLH}	DIR	B	10	35	10	30	ns
t _{PHL}			15	40	15	35	

NOTE 1: For load circuit and voltage waveforms, see page 1-12.

2 ALS AND AS CIRCUITS

**TYPES SN54AS640 THRU SN54AS645
SN74AS640 THRU SN74AS645
OCTAL BUS TRANSCEIVERS**

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: All inputs	7 V
I/O ports	5.5 V
Operating free-air temperature range: SN54AS640, SN54AS643, SN54AS645	-55 °C to 125 °C
SN74AS640, SN74AS643, SN74AS645	0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

recommended operating conditions

		SN54AS640			SN74AS640			UNIT	
		SN54AS643			SN74AS643				
		SN54AS645			SN74AS645				
		MIN	NOM	MAX	MIN	NOM	MAX		
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V	
V_{IH}	High-level input voltage	2			2			V	
V_{IL}	Low-level input voltage	0.8			0.8			V	
I_{OH}	High-level output current	-12			-15			mA	
I_{OL}	Low-level output current	48			64			mA	
T_A	Operating free-air temperature	-55			0			70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54AS ¹			SN74AS ¹			UNIT
		MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}	$V_{CC} = 4.5$ V, $I_I = -18$ mA	-1.2			-1.2			V
V_{OH}	$V_{CC} = 4.5$ V to 5.5 V, $I_{OH} = -2$ mA	$V_{CC}-2$			$V_{CC}-2$			V
	$V_{CC} = 4.5$ V, $I_{OH} = -3$ mA	2.4	3.2		2.4	3.2		
	$V_{CC} = 4.5$ V, $I_{OH} = -12$ mA	2.4						
	$V_{CC} = 4.5$ V, $I_{OH} = -15$ mA				2.4			
V_{OL}	$V_{CC} = 4.5$ V, $I_{OL} = 48$ mA	0.30	0.55					V
	$V_{CC} = 4.5$ V, $I_{OL} = 64$ mA				0.35	0.55		
I_I	Control inputs	$V_{CC} = 5.5$ V, $V_I = 7$ V			0.1			mA
	A or B ports	$V_{CC} = 5.5$ V, $V_I = 5.5$ V			0.1			
I_{IH}	Control inputs	$V_{CC} = 5.5$ V, $V_I = 2.7$ V			20			μ A
	A or B ports‡				50			
I_{IL}	Control inputs	$V_{CC} = 5.5$ V, $V_I = 0.4$ V			-0.5			mA
	A or B ports‡				-0.75			
I_{O5}	$V_{CC} = 5.5$ V, $V_O = 2.25$ V	-30		-112	-30		-112	mA
I_{CC}	'AS640	$V_{CC} = 5.5$ V	Outputs high	37	58	37	58	mA
			Outputs low	78	123	78	123	
	Outputs disabled		51	80	51	80		
	'AS643		Outputs high	48	79	48	79	
			Outputs low	88	143	88	143	
	'AS645		Outputs disabled	61	100	61	100	
			Outputs high	62	97	62	97	
	Outputs low		95	149	95	149		
	Outputs disabled		79	123	79	123		

†All typical values are at $V_{CC} = 5$ V, $T_A = 25$ °C

‡For I/O ports, the parameters I_{IH} and I_{IL} include the off-state output current.

§The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS} .

2
ALS AND AS CIRCUITS

**TYPES SN54AS640 THRU SN54AS645
SN74AS640 THRU SN74AS645
OCTAL BUS TRANSCEIVERS**

'AS640 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_1 = 500 \Omega,$ $R_2 = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54AS640		SN74AS640		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	2	8	2	7	ns
t _{PHL}			2	7	2	6	
t _{PZH}	\bar{G}	A or B	2	10	2	8	ns
t _{PZL}			2	12	2	10	
t _{PHZ}	\bar{G}	A or B	2	9	2	8	ns
t _{PLZ}			2	16	2	13	

'AS643 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_1 = 500 \Omega,$ $R_2 = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54AS643		SN74AS643		
			MIN	MAX	MIN	MAX	
t _{PLH}	A	B	2	10	2	8	ns
t _{PHL}			2	7.5	2	7	
t _{PLH}	B	A	2	11.5	2	10	ns
t _{PHL}			2	10	2	9	
t _{PZH}	\bar{G}	A	2	13	2	11	ns
t _{PZL}			2	13	2	11	
t _{PHZ}	\bar{G}	A	2	8.5	2	7.5	ns
t _{PLZ}			2	12	2	10.5	
t _{PZH}	\bar{G}	B	2	11.5	2	10	ns
t _{PZL}			2	12	2	10	
t _{PHZ}	\bar{G}	B	2	8	2	7	ns
t _{PLZ}			2	12	2	10	

'AS645 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_1 = 500 \Omega,$ $R_2 = 500 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54AS645		SN74AS645		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	2	11	2	9.5	ns
t _{PHL}			2	10.5	2	9	
t _{PZH}	\bar{G}	A or B	2	12	2	11	ns
t _{PZL}			2	12	2	10	
t _{PHZ}	\bar{G}	A or B	2	8	2	7	ns
t _{PLZ}			2	13	2	12	

NOTE 1: For load circuit and voltage waveforms, see page 1-12.

**TYPES SN54AS640 THRU SN54AS645
SN74AS640 THRU SN74AS645
OCTAL BUS TRANSCEIVERS**

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)

Supply voltage, V_{CC}	7 V
Input voltage: All inputs and I/O ports	7 V
Operating free-air temperature range: SN54AS641, SN54AS642, SN54AS644	-55 °C to 125 °C
SN74AS641, SN74AS642, SN74AS644	0 °C to 70 °C
Storage temperature range	-65 °C to 150 °C

recommended operating conditions

		SN54AS641			SN74AS641			UNIT		
		SN54AS642			SN74AS642					
		SN54AS644			SN74AS644					
		MIN	NOM	MAX	MIN	NOM	MAX			
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V		
V_{IH}	High-level input voltage	2			2			V		
V_{IL}	Low-level input voltage	0.8			0.8			V		
V_{OH}	High-level output voltage	5.5			5.5			V		
I_{OL}	Low-level output current	48			64			mA		
T_A	Operating free-air temperature	-55			125			0	70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS	SN54AS641			SN74AS641			UNIT	
		SN54AS642			SN74AS642				
		SN54AS644			SN74AS644				
		MIN	TYP†	MAX	MIN	TYP†	MAX		
V_{IK}	$V_{CC} = 4.5 V$, $I_I = -18 mA$	-1.2			-1.2			V	
I_{OH}	$V_{CC} = 4.5 V$, $V_{OH} = 5.5 V$	0.1			0.1			mA	
V_{OL}	$V_{CC} = 4.5 V$, $I_{OL} = 48 mA$	0.3			0.55			V	
	$V_{CC} = 4.5 V$, $I_{OL} = 64 mA$				0.35				
I_I	Control inputs	$V_{CC} = 5.5 V$, $V_I = 7 V$			0.1			mA	
	A or B ports	$V_{CC} = 5.5 V$, $V_I = 5.5 V$			0.1				
I_{IH}	Control inputs	$V_{CC} = 5.5 V$, $V_I = 2.7 V$			20			µA	
	A or B ports‡				50				
I_{IL}	Control inputs	$V_{CC} = 5.5 V$, $V_I = 0.4 V$			-0.5			mA	
	A or B ports‡				-0.75				
I_{CC}	'AS641	$V_{CC} = 5.5 V$	Outputs high		50	82	50	82	mA
			Outputs low		84	136	84	136	
			Outputs high		25	42	25	42	
			Outputs low		64	104	64	104	
			Outputs high		38	62	38	62	
			Outputs low		76	124	76	124	

†All typical values are at $V_{CC} = 5 V$, $T_A = 25 °C$
‡For I/O ports, the parameters I_{IH} and I_{IL} include the off-state output current.

2

ALS AND AS CIRCUITS

**TYPES SN54AS640 THRU SN54AS645
SN74AS640 THRU SN74AS645
OCTAL BUS TRANSCEIVERS**

'AS641 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_L = 680 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54AS641		SN74AS641		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	5	23	5	21	ns
t _{PHL}			1	8.5	1	7.5	
t _{PLH}	\bar{C}	A or B	5	24	5	21	ns
t _{PHL}			1	10	1	9	
t _{PLH}	DIR	A or B	5	26	5	22	ns
t _{PHL}			1	11	1	10	

'AS642 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_L = 680 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54AS642		SN74AS642		
			MIN	MAX	MIN	MAX	
t _{PLH}	A or B	B or A	5	28.5	5	24	ns
t _{PHL}			1	8.5	1	7.5	
t _{PLH}	\bar{C}	A or B	5	25	5	22	ns
t _{PHL}			1	11	1	10	
t _{PLH}	DIR	A or B	5	26.5	5	23.5	ns
t _{PHL}			1	12.5	1	11.5	

'AS644 switching characteristics (see Note 1)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	$V_{CC} = 4.5 \text{ V to } 5.5 \text{ V,}$ $C_L = 50 \text{ pF,}$ $R_L = 680 \Omega,$ $T_A = \text{MIN to MAX}$				UNIT
			SN54AS644		SN74AS644		
			MIN	MAX	MIN	MAX	
t _{PLH}	A	B	5	28.5	5	24	ns
t _{PHL}			1	8.5	1	7.5	
t _{PLH}	B	A	5	23	5	21	ns
t _{PHL}			1	8.5	1	7.5	
t _{PLH}	\bar{C}	A or B	5	24	5	21	ns
t _{PHL}			1	10	1	9	
t _{PLH}	DIR	A or B	5	26	5	22	ns
t _{PHL}			1	11	1	10	

NOTE 1: For load circuit and voltage waveforms, see page 1-12.

2 ALS AND AS CIRCUITS

PRODUCT PREVIEW

2-454 This page contains information on a product under development. Texas Instruments reserves the right to change or discontinue this product without notice.

**TEXAS
INSTRUMENTS**

POST OFFICE BOX 225012 • DALLAS, TEXAS 75265