

CP-30Y

SMT/ Desoldering Products

STAINLESS STEEL MOUTH width : 3.0mm



RMA base flux.

JAN Code:4975205310215

- [Specifications](#)

MODEL	Type	Width	Length
CP-15Y		Approx. 1.5mm	
CP-20Y	Plain Knitting	Approx. 2.0mm	
CP-25Y		Approx. 2.5mm	Approx. 2m
CP-30Y		Approx. 3.0mm	
CP-35Y	Tubular Knitting	Approx. 3.5mm	

- [Features](#)

FOR LEAD-FREE DESOLDERING

Our thin and soft desoldering wire's flat braid has efficient thermal transmission. Removes solder faster with better heat response than previous wicks. Recommended for lead-free solder with high heating load.



DISPENSER PACK WITH STAINLESS STEEL MOUTH

Can be used for precision PCBs safely. Ergonomic design will keep your fingers cool.



SPECIFICATIONS

Rosin	Length	Width						Quantity	
		1.0 mm	1.5 mm	2.0 mm	2.5 mm	3.0 mm	3.5 mm		
HALOGEN-FREE	1.5 m			CPN-2015-10				10	
						CPN-3015-10		10	
RMA flux	1.5 m	CP-1015	CP-1515					1	
		CP-1015-10	CP-1515-10					10	
				CP-2015				1	
				CP-2015-10				10	
					CP-2515			1	
					CP-2515-10			10	
						CP-3015		1	
						CP-3015-10		10	
							CP-3515	1	
							CP-3515-10	10	
	2.0m			CP-15Y				1	
					CP-20Y			1	
						CP-25Y		1	
							CP-30Y	1	
								CP-35Y	1
									1
	13m							1	
	15m						CP-35B	1	
	20m					CP-25B		1	
							CP-30B	1	
30m		CP-10B	CP-15B				1		
				CP-20B			1		