


1. SPECIFICATION

AK-503205-MM-1

ITEM		SPECIFICATIONS	
01	Type	Dynamic speaker	
02	Dimension	External diameter 50 mm	
03	Rated Input Power	0.5W	
04	Max. Input Power	1.0 W for 1 minute	
05	Impedance	$32\Omega \pm 15\%$ at 1KHz 1V	
06	Resonance Frequency (Fo)	550Hz \pm 20% at Fo, 1V	
07	Sound pressure level	96 dB(0.5W/0.1M) \pm 3 dB	at AVE0.8, 1.0,1.2, 1.5 KHz.
08	Frequency Range	Fo – 4 K Hz	
09	Total Harmonics Distortion	Max 10 % at 1 KHz, 0.1W.	

REV NO.	REVISION NOTE	APPROVAL	DATE
---------	---------------	----------	------



RoHS

TITLE: DYNAMIC SPEAKER		DRAWN: Zack 2020/02/18	SCALE: 2:1	SHEET: 1:1
PART NO. AK-503205-MM-1		DESIGNED: R&D OF AAT	UNITS: mm	
DWG NO. CXS50115-R32W0.5-N12.5M-G	2 REV	CHECKED:	TOLERANCE ± 0.5	
		APPROVAL:	UNLESS OTHERWISE SPECIFIED:	
		MATERIAL: SPCC	ONE PLACE DECIMAL \pm ***	
			TWO PLACE DECIMAL \pm ***	
			THREE PLACE DECIMAL \pm ***	



ADVANCED ACOUSTIC TECHNOLOGY CORPORATION

For more information, please contact AATC.

AATC

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[AATC:](#)

[AK-503205-MM-1](#)