

## USB-Logo Programming Cable for Siemens Logo! USB Version PLC 6ED1 057-1AA01-0BA0



- Compatible with OS: Windows2000/Windows XP ( Windows NT/95/98/Me/Vista/Win7/DOS/Linux/Mac NOT SUPPORTED )
- Cable Length: 3 Meters
- Support USB-CABLE programming software version LOGO! Soft V4.0 and above
- Power supplied by USB bus and the programming port of LOGO! Controller.

### Product description

SIEMENS LOGO USB-LOGO Isolated Cable 6ED1 057-1AA00-0BA0 PLC CABLE

#### -Descriptions:

LOGO! USB-CABLE is a programming cable which use the USB interface to achieve the serial connection and the conversion of peripheral port signal. Cable programming is provided through the USB interface connector and serial peripherals signal converter

programming, under the control of computer operation, simulating the computer's USB interface to traditional serial (commonly known as COM port), thus using the current programming software, communicating software and monitoring software. The work power of the cable comes from USB port and programming port of LOGO controller.

USB-LOGO CABLE is photoelectric isolated, can be applied to LOGO Controller, especially the industrial fields with greater interference and easily damaged communication port. All kinds of protection measures in the circuit give promise to the safe operation of the system.

**- Features:**

Compatible with OS: Windows2000/Windows XP ( Windows NT/95/98/Me/Vista/Win7/DOS/Linux/Mac NOT SUPPORTED )

Cable Length: 3 Meters

Support USB-CABLE programming software version LOGO! Soft V4.0 and above

Power supplied by USB bus and the programming port of LOGO! Controller

Optical isolation voltage 1000VDC

Support UART data format Data 8, stop bit 1, 2, check odd/even/no parity

Each PC only supports one USB cable Working temperature -20~+75°C