


1104 KSS PCB Support




- Material: UL approved Nylon 66, 94V-2.
- Color: Natural.
- Stand on design to lock Print circuit board.
- No tool is needed and easy to fix or remove from PC board.



Standard Design




RS-3, 6B




RS-6C, 12C




RS-6A, 7A, 10A



RS-8S



RS-10L



RS-10, 10S, 12H

Unit: mm

Item No.	A	PCB		Chassis		Packing
		hole	thickness	hole	thickness	
<input type="checkbox"/> RS-2D	2.5	4.0	1.8	5.0	3.2	100 pcs / Bag
<input type="checkbox"/> RS-3	3.5	4.0	1.8	5.5	1.4	
<input type="checkbox"/> RS-5	5.0	4.0	1.8	5.5	1.8	
<input type="checkbox"/> RS-5D	5.0	4.0	1.8	5.0	3.2	
<input type="checkbox"/> RS-5S	5.0	3.0	1.7	4.8	2.0	
<input type="checkbox"/> RS-6	6.1	4.0	1.8	5.5	1.8	
<input type="checkbox"/> RS-6A	5.6	4.0	1.6	6.4	1.8	
<input type="checkbox"/> RS-6B	5.6	4.0	1.8	6.4	1.4	
<input type="checkbox"/> RS-6C	6.1	4.2	1.8	5.2	1.4	
<input type="checkbox"/> RS-6S	5.9	3.5	1.8	5.3	1.8	
<input type="checkbox"/> RS-7A	6.6	4.0	1.6	5.4	1.6	
<input type="checkbox"/> RS-8	8.0	4.0	1.8	5.5	1.8	
<input type="checkbox"/> RS-8S	6.1	4.0	1.6	5.5	1.8	
<input type="checkbox"/> RS-10	9.8	4.0	1.8	5.5	1.8	
<input type="checkbox"/> RS-10S	9.3	4.0	1.6	5.5	1.8	
<input type="checkbox"/> RS-10A	9.8	4.0	1.6	5.4	1.8	
<input type="checkbox"/> RS-10L	9.8	4.0	1.6	5.5	1.8	
<input type="checkbox"/> RS-12	12.0	4.0	1.8	5.5	1.8	
<input type="checkbox"/> RS-12C	12.1	4.2	1.8	5.2	1.4	
<input type="checkbox"/> RS-12H	11.8	4.0	1.6	5.5	1.8	
<input type="checkbox"/> RS-14	14.0	4.0	1.8	5.5	1.8	
<input type="checkbox"/> RS-18	18.0	4.0	1.8	5.5	1.8	