

**SPECIFICATION**  
 1. Material: HIGH-TEMP Plastic:UL94V-0,color:Red/Buff.  
 HIGH-TEMP Plastic:UL94V-0,color:Black.  
 Lock: Copper alloy.  
 Solder tab: Copper alloy.  
 2. Electrical Characteristics:  
 Current rating: 0.25A(max).  
 Voltage rating: 50V(max), -25°C~+85°C.  
 Insulating resistance: 500M ohms min. at 500V DC.  
 Dielectric withstanding voltage: 500V AC/minute.  
 Contact resistance: 30m ohms max.

Pin#	A	B	C	Pin位	A	B	C
4	1.5	2.56	6.4	33	16	17.06	20.9
5	2	3.06	6.9	34	16.5	17.56	21.4
6	2.5	3.56	7.4	35	17	18.06	21.9
7	3	4.06	7.9	36	17.5	18.56	22.4
8	3.5	4.56	8.4	37	18	19.06	22.9
9	4	5.06	8.9	38	18.5	19.56	23.4
10	4.5	5.56	9.4	39	19	20.06	23.9
11	5	6.06	9.9	40	19.5	20.56	24.4
12	5.5	6.56	10.4	41	20	21.06	24.9
13	6	7.06	10.9	42	20.5	21.56	25.4
14	6.5	7.56	11.4	43	21	22.06	25.9
15	7	8.06	11.9	44	21.5	22.56	26.4
16	7.5	8.56	12.4	45	22	23.06	26.9
17	8	9.06	12.9	46	22.5	23.56	27.4
18	8.5	9.56	13.4	47	23	24.06	27.9
19	9	10.06	13.9	48	23.5	24.56	28.4
20	9.5	10.56	14.4	49	24	25.06	28.9
21	10	11.06	14.9	50	24.5	25.56	29.4
22	10.5	11.56	15.4	51	25	26.06	29.9
23	11	12.06	15.9	52	25.5	26.56	30.4
24	11.5	12.56	16.4	53	26	27.06	30.9
25	12	13.06	16.9	54	26.5	27.56	31.4
26	12.5	13.56	17.4	55	27	28.06	31.9
27	13	14.06	17.9	56	27.5	28.56	32.4
28	13.5	14.56	18.4	57	28	29.06	32.9
29	14	15.06	18.9	58	28.5	29.56	33.4
30	14.5	15.56	19.4	60	29.5	30.56	34.4
31	15	16.06	19.9	64	31.5	32.56	36.4
32	15.5	16.56	20.4	68	33.5	34.56	38.4
				80	39.5	40.56	44.4

适用FPC寸法  
 APPLICABLE FPC


适用线路板  
 RECOMMENDED PCB LAYOUT

**CSCONN**

CSCONN PRECISE ELECTRONICS CO., LTD

UNITS: mm	
GENERAL TOLERANCE	PART NO. (INTENDED USE)
X.° ±5° 0.X±0.25	CFP05XXX03001
X.1±2° 0.XX±0.2	APPD:
XX±1° 0.XXX±0.1	CHKD: Skila
	DR: Kitty

TITLE: FPC 0.5MM XP SMT掀盖式  
 DWG NO. FPC



SCALE 1:1  
 SHEET 1 OF 1  
 REV A