# **Right Angle HD 68 Female SCSI Connector**



Starte right angle SCSI DB 68 female connector with latch bracket for PCB, this 90 degree HD 68 pin female SCSI connector pin arrangement in two rows, one on top of the other. The top row has 34 pins and the lower row has 34 pins. It is usually used on the Industrial equipment PCB and SCSI...

## **Product Details**

Starte right angle SCSI DB 68 female connector with latch bracket for PCB, this 90 degree HD 68 pin female SCSI connector pin arrangement in two rows, one on top of the other. The top row has 34 pins and the lower row has 34 pins. It is usually used on the Industrial equipment PCB and SCSI devices, such as SCSI servo, SCSI PCI card and motion controller.

## Product Parameters of right angle DB68 female PCB connector:

Item 90 degree SCSI-3 female connector with clip

Brand Starte

Product type SCSI cable and connector

No. Of Contact 68 pin

Contact Type Female, header right-angle mount type

Options Latch Bracket

Threaded Finishes #2-56

Contact Finishes Gold Selective Plating

Pin Layout Standard MOQ 1 PCS Sample Free Package Bags Warranty Two years

## Technical Parameters of angled 68 pin female PCB SCSI Connector:

## **Connector Material**

Housing Plastic Thermoplastic Nylon PA9T UL94V-0, Black

Contacts
Copper Alloy Gold Selective Plated
Front Shell
Steel, Nickel Plated Over Copper
Bracket
Steel, Nickel Plated Over Copper
Copper Tin Plated Over Copper

**Electrical Characterisitics** 

Contact Current Rating 0.5 Amp
Dielectric Withstanding Voltage 150V AC
Insulation Resistance 500M $\Omega$ / Min
Contact Resistance 35m $\Omega$  /Max
Operation Temperature -55°C $\sim$ +85°C

## **Application of right angle SCSI-3 68 pin female connector:**

- 1)SCSI motion controller, Serial PCIx card
- 2)SCSI Servers machines and Drive enclosures equipments,
- 3)RAIDs,CD ROM,File Server board
- 4)SCSI breakout Board, SCSI line tester