

Surface Mount Type

POSCAP



Series : **TPE**

Size : **B**

Features

- Small size (L 3.5×W 2.8×H 1.9 mm)
- Low ESR (15 mΩ)
- RoHS compliance, Halogen free

Specifications

Size code	B2	
Category temperature range	-55 °C to +105 °C	
Rated voltage range	2.0 V.DC to 10 V.DC	
Category voltage range	1.8 V.DC to 8.0 V.DC	
Rated capacitance range	47 μF to 470 μF	
Capacitance tolerance	±20 % (120 Hz / + 20 °C)	
Leakage current	Please see the attached characteristics list	
Dissipation factor (tan δ)	Please see the attached characteristics list	
Surge voltage (V.DC)	Rated voltage × 1.15	
Endurance	+105 °C, 1000 h rated voltage applied	
	* Rated temp, +85 °C Products : +85 °C, 1000 h, rated voltage applied	
	Capacitance change	Within ±20 % of the initial value
	tan δ	≤ 1.5 times of the initial limit
Damp heat (Steady State)	DC leakage current	Within the initial limit
	+60 °C, 90 % to 95 %, 500 h, No-applied voltage	
	Capacitance change	Within +50 %, -20 % of the initial value (2R5TPE220MAZB (MAPB, MAFB), 2R5TPE330MAZB, 2TPE330MAFB (MADGB), 2TPE470MAJGB (MAFB), 2TPE330MFB, ETPE330MAFB (MA9GB))
	tan δ	Within +40 %, -20 % of the initial value (Except for above model)
	DC leakage current	≤ 3 times of the initial limit

Marking

R. Voltage (V.DC)	2.0	2.5	4.0	6.3	8.0	10.0	
Code	d	e	g	j	k	A	
R. Cap. (μF)	47	100	120	150	220	330	470
Code	S7	A8	C8	E8	J8	N8	S8

Dimensions (not to scale)

Unit : mm

Size code	L±0.2	W±0.2	H±0.1	S±0.2	W1±0.1
B2	3.5	2.8	1.9	0.8	2.2

* Externals of figure are the reference.

Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (μF)	Case size (mm)			Size code	Specifications				Standard		Floor life		
						L	W	H		Ripple* ¹ current (mA r.m.s.)	ESR* ² (mΩ max.)	tan δ* ³	LC* ⁴ (μA)	Part number	Min. Packaging Qty (pcs)	Reflow Temp ≤ 260°C	Reflow Temp ≤ 250°C	
TPE	2	105	2.0	105	330	3.5	2.8	1.9	B2	2000	15	0.08	132.0	2TPE330MFB	2000	3	3	
		85	1.8	105		3.5	2.8	1.9		2000	15	0.08	132.0	2TPE330MAFB	2000			
		85	1.8	105		3.5	2.8	1.9		2000	13/300 kHz	0.10	132.0	2TPE330MADGB	2000			
		85	1.8	105	470	3.5	2.8	1.9		2300	15	0.10	188.0	2TPE470MAFB	2000			
		85	1.8	105		3.5	2.8	1.9		2300	11/300 kHz	0.08	188.0	2TPE470MAJGB	2000			
	2.5	85	2.0	105	220	3.5	2.8	1.9		2000	15	0.08	110.0	2R5TPE220MAFB	2000			
		105	2.5	105		3.5	2.8	1.9		1800	15/300 kHz	0.08	110.0	2R5TPE220MFGB	2000			
		105	2.5	105		3.5	2.8	1.9		1700	21	0.08	55.0	2R5TPE220MLB	2000			
		85	2.0	105		3.5	2.8	1.9		1600	25	0.08	55.0	2R5TPE220MAPB	2000			
		105	2.5	105		3.5	2.8	1.9		1400	35	0.08	55.0	2R5TPE220MZB	2000			
		85	2.0	105		3.5	2.8	1.9		1400	35	0.08	55.0	2R5TPE220MAZB	2000			
		85	2.0	105	330	3.5	2.8	1.9		1400	35	0.08	82.5	2R5TPE330MAZB	2000			
		85	2.0	105		3.5	2.8	1.9		3200	9/300 kHz	0.08	165.0	ETPE330MA9GB	2000			
		NEW	105	2.0		105	3.5	2.8		1.9	3200	9/300 kHz	0.08	165.0	ETPE330M9GB			2000
		NEW	85	2.0		105	3.5	2.8		1.9	2700	15	0.08	165.0	ETPE330MAFB			2000
		NEW	105	2.0		105	3.5	2.8		1.9	2700	15	0.08	165.0	ETPE330MFB			2000
		4	105	4.0		105	100	3.5		2.8	1.9	1400	35	0.08	40.0			4TPE100MZB
	85		3.2	105	150	3.5	2.8	1.9		1400	35	0.08	60.0	4TPE150MAZB	2000			
	85		3.2	105	220	3.5	2.8	1.9		1400	35	0.08	88.0	4TPE220MAZB	2000			
	6.3	105	6.3	105	100	3.5	2.8	1.9		1600	25	0.08	63.0	6TPE100MPB	2000			
		85	5.0	105		3.5	2.8	1.9		1400	35	0.08	63.0	6TPE100MAZB	2000			
		105	6.3	105		3.5	2.8	1.9		1400	35	0.08	63.0	6TPE100MZB	2000			
		85	5.0	105	120	3.5	2.8	1.9		1400	35	0.08	75.6	6TPE120MAZB	2000			
		85	5.0	105		3.5	2.8	1.9		1600	25	0.08	94.5	6TPE150MAPB	2000			
		85	5.0	105	150	3.5	2.8	1.9		1400	35	0.08	94.5	6TPE150MAZB	2000			
		85	5.0	105		3.5	2.8	1.9		1400	35	0.10	138.6	6TPE220MAZB	2000			
		NEW	85	5.0	105	220	3.5	2.8		1.9	1600	25	0.10	138.6	6TPE220MAPB			2000
	8	85	6.3	105	3.5		2.8	1.9		1400	35	0.08	80.0	8TPE100MAZB	2000			
	10	85	8.0	105	47	3.5	2.8	1.9		1400	35	0.08	47.0	10TPE47MAZB	2000			

*1 Ripple current (100 kHz/+45 °C), *2 ESR (100 kHz/+20 °C) *3 tan δ (120 Hz/+20 °C) *4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".

Surface Mount Type

POSCAP

Series : TPE

Size : D




Features

- Low profile (Height 1.5 mm max.)
- Low ESR (7 mΩ)
- Large capacitance (1500 μF max.)
- RoHS compliance, Halogen free

Specifications


Size code	D15E	D2E	D3L	D4
Category temperature range	-55 °C to +105 °C			
Rated voltage range	6.3 V.DC	2.5 V.DC to 10 V.DC		
Category voltage range	5.0 V.DC	2.5 V.DC to 10 V.DC		
Rated capacitance range	470 μF	68 μF to 470 μF	220 μF to 680 μF	330 μF to 1500 μF
Capacitance tolerance	±20 % (120 Hz / + 20 °C)			
Leakage current	Please see the attached characteristics list			
Dissipation factor (tan δ)	Please see the attached characteristics list			
Surge voltage (V.DC)	Rated voltage × 1.15			
Endurance	+105 °C, 2000 h rated voltage applied * Rated temp, +85 °C Products : +85 °C, 1000 h, rated voltage applied 6TPE330MAP, 6TPE470MAZU : +85 °C, 2000 h,			
	Capacitance change	Within ±20 % of the initial value		
	tan δ	≤ 1.5 times of the initial limit		
	DC leakage current	Within the initial limit		
Damp heat (Steady State)	+60 °C, 90 % to 95 %, 500 h, No-applied voltage			
	Capacitance change	Within +50 %, -20 % of the initial value (2R5TPE220M (I, F, 9), 2R5TPE330M (I, F, C, 9, 7), 2R5TPE470M (I, F, C, 9, 7), 2R5TPE1000MF, 2R5TPE1500M (F, C))		
		Within +40 %, -20 % of the initial value (Except for above model)		
	tan δ	≤ 1.5 times of the initial limit		
DC leakage current	≤ 3 times of the initial limit			

Marking



R. Voltage (V.DC)	2.5	4.0	6.3	10.0
Code	e	g	j	A

Dimensions (not to scale)



Unit : mm

Size code	L±0.3	W±0.2	H±0.2*1	S±0.2	W1±0.1
D15E	7.3	4.3	1.4	1.1	2.4
D2E	7.3	4.3	1.8	1.3	2.4
D3L	7.3	4.3	2.8	1.3	2.4
D4	7.3	4.3	3.8	1.3	2.4

* Externals of figure are the reference.

* 1 ±0.1 :D15E, D2E

Characteristics list

Series	Rated voltage (V.DC)	Rated temp. (°C)	Category voltage (V.DC)	Category temp. (°C)	Rated capacitance (μF)	Case size (mm)			Size code	Specifications				Standard		Floor life				
						L	W	H		Ripple current (mA r.m.s.) ^{*1}	ESR ^{*2} (mΩ max.)	tan δ ^{*3}	LC ^{*4} (μA)	Part number	Min. Packaging Qty (pcs)	Reflow Temp ≤260°C	Reflow Temp ≤250°C			
TPE	2.5	105	2.5	105	220	7.3	4.3	1.8	D2E	3900	9	0.10	55.0	2R5TPE220M9	3000	3				
						7.3	4.3	1.8		3100	15	0.10	55.0	2R5TPE220MF	3000					
						7.3	4.3	1.8		2800	18	0.10	55.0	2R5TPE220MI	3000					
		7.3	4.3	1.8	2400	25	0.10	55.0		2R5TPE220M	3000									
		7.3	4.3	1.8	4400	7	0.10	82.5		2R5TPE330M7	3000									
		7.3	4.3	1.8	3900	9	0.10	82.5		2R5TPE330M9	3000									
		7.3	4.3	1.8	3500	12	0.10	82.5		2R5TPE330MC	3000									
		7.3	4.3	1.8	3100	15	0.10	82.5		2R5TPE330MF	3000									
		7.3	4.3	1.8	2800	18	0.10	82.5		2R5TPE330MI	3000									
		7.3	4.3	1.8	2400	25	0.10	82.5		2R5TPE330M	3000									
		7.3	4.3	1.8	4400	7	0.10	117.5		2R5TPE470M7	3000									
		7.3	4.3	1.8	3900	9	0.10	117.5		2R5TPE470M9	3000									
		7.3	4.3	1.8	3500	12	0.10	117.5		2R5TPE470MC	3000									
		7.3	4.3	1.8	3100	15	0.10	117.5		2R5TPE470MF	3000									
		7.3	4.3	1.8	2800	18	0.10	117.5		2R5TPE470MI	3000									
	7.3	4.3	2.8	3500	12	0.10	170.0	2R5TPE680MCL	2500											
	7.3	4.3	2.8	3100	15	0.10	170.0	2R5TPE680MFL	2500											
	7.3	4.3	3.8	1000	D4	3900	15	0.15	250.0	2R5TPE1000MF	2000	-								
	7.3	4.3	3.8	4400		12	0.15	375.0	2R5TPE1500MC	2000										
	7.3	4.3	3.8	3900		15	0.15	375.0	2R5TPE1500MF	2000										
	4	105	4.0	105	150	7.3	4.3	1.8	D2E	2800	18	0.10	60.0	4TPE150MI	3000	2a				
										3100	15	0.10	88.0	4TPE220MF	3000					
										2800	18	0.10	88.0	4TPE220MI	3000					
		2400	25	0.10	88.0	4TPE220M	3000													
		2800	18	0.10	132.0	4TPE330MI	3000													
		2400	25	0.10	132.0	4TPE330M	3000													
		7.3	4.3	2.8	3500	12	0.10	188.0		4TPE470MCL	2500									
		7.3	4.3	2.8	3100	15	0.10	188.0		4TPE470MFL	2500									
		7.3	4.3	2.8	2800	18	0.10	188.0		4TPE470MIL	2500									
		7.3	4.3	2.8	2400	25	0.10	188.0		4TPE470ML	2500									
6.3		105	6.3	105	100	7.3	4.3	1.8		D2E	2800	18	0.10	63.0	6TPE100MI			3000	3	
											2400	25	0.10	63.0	6TPE100M			3000		
											3100	15	0.10	94.5	6TPE150MF			3000		
		2800	18	0.10	94.5	6TPE150MI	3000													
		2400	25	0.10	94.5	6TPE150M	3000													
	2800	18	0.10	138.6	6TPE220MI	3000														
	2400	25	0.10	138.6	6TPE220M	3000														
	7.3	4.3	1.8	2400	25	0.10	138.6	6TPE220MAP	3000											
	7.3	4.3	1.8	2400	25	0.10	207.9	6TPE330MAP	3000											
	7.3	4.3	2.8	2400	25	0.10	207.9	6TPE330MAL	2500											
	7.3	4.3	2.8	3900	9/500 kHz	0.10	207.9	6TPE330MA9EL	2500											
	7.3	4.3	2.8	3100	15	0.10	207.9	6TPE330MFL	2500											
7.3	4.3	2.8	2800	18	0.10	207.9	6TPE330MIL	2500												
7.3	4.3	2.8	2400	25	0.10	207.9	6TPE330ML	2500												
7.3	4.3	3.8	4400	10	0.10	207.9	6TPE330MAA	2000												
7.3	4.3	1.4	1700	35	0.10	296.1	6TPE470MAZU	4000												
7.3	4.3	3.8	3500	18	0.15	296.1	6TPE470MI	2000												
7.3	4.3	3.8	3000	25	0.15	296.1	6TPE470M	2000												
7.3	4.3	3.8	3500	18	0.15	428.4	6TPE680MI	2000												
7.3	4.3	3.8	3000	25	0.15	428.4	6TPE680M	2000												
10	105	10.0	105	68	7.3	4.3	1.8	D2E	2400	25	0.10	68.0	10TPE68M	3000	-					
								D3L	2800	18	0.10	220.0	10TPE220MIL	2500						
	D3L	2400	25	0.10	220.0	10TPE220ML	2500													
	D4	3000	25	0.10	330.0	10TPE330M	2000													

*1 Ripple current (100 kHz/ +45 °C), *2 ESR (100 kHz/+20 °C) *3 tan δ (120 Hz/+20 °C) *4 After 5 minutes

◆ Please refer to each page in this catalog for "Reflow conditions" and "Taping specifications".