



element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[CPRP010-W](#)

[CPRP020-W](#)

[CPRP010-B](#)


[CPRP020-B](#)

EN
This Datasheet is presented by
the manufacturer

DE
Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR
Cette fiche technique est
présentée par le fabricant

Official Raspberry Pi HDMI Cable






- The official Raspberry Pi HDMI cable has been engineered to maximise the performance and functionality of your Raspberry Pi 3. (Backward compatible with all previous generations of Raspberry Pi).
- Triple layer shielding allows you to get the best performance from your Wi-Fi and Bluetooth connectivity with your Raspberry Pi 3.
- Different cable options to suit your project - Choose between 1M & 2M cable lengths in either Black or White. Meets the very latest HDMI Version 2.0 standards.

Part Number	Colour	Length
CPRP010-W	White	1M
CPRP020-W	White	2M
CPRP010-B	Black	1M
CPRP020-B	Black	2M



Official Raspberry Pi HDMI Cable



**5P+4C(30AWG)
2.0 Version**

Type A PIN	Signal Assignment	Type A PIN
1 Blue		Blue 1
2 ground		ground 2
3 white		white 3
4 Blue		Blue 4
5 ground		ground 5
6 white		white 6
7 Blue		Blue 7
8 ground		ground 8
9 white		white 9
10 Blue		Blue 10
11 ground		ground 11
12 white		white 12
14 Blue		Blue 14
17 ground		ground 17
19 white		white 19
15 Yellow		Yellow 15
15 Orange		Orange 15
15 white		white 15
15 red		red 15
SHELL		SHELL

LENGTH(m)
1 - 0.03
2 - 0.05

Features

Nickel Plated Connectors
RoHS Compliant
2160P

Electrical Specifications

Withstanding Voltage 300V DC 0.1 Sec.
Insulation Resistance 3M ohm 300V DC

- 30/6.0 HDMI cable full 19+1 pins, 30AWG, 6.0MM
- 2.0 Version with Ethernet and Audio return channel
- Nickel plated contact to resist corrosion and for optimum connection and maximum signal transfer
- Triple shielded to protect signal: Two layers of Aluminium Mylar & One layer of Aluminium Magnesium (128 Strand)
- RoHS soft PVC jacket for lifetime protection
- Pure Oxygen-free copper for ultimate conductivity
- Support 3D,4K*2K,17.8Gbps,2160P/60Hz and X.V.color





element14

EN - For pricing and availability in your local country please visit one of the below links:

DE - Informationen zu Preisen und Verfügbarkeit in Ihrem Land erhalten Sie über die unten aufgeführten Links:

FR - Pour connaître les tarifs et la disponibilité dans votre pays, cliquez sur l'un des liens suivants:

[CPRP010-W](#)

[CPRP020-W](#)

[CPRP010-B](#)

[CPRP020-B](#)

EN
This Datasheet is presented by
the manufacturer

DE
Dieses Datenblatt wird vom
Hersteller bereitgestellt

FR
Cette fiche technique est
présentée par le fabricant